

- 6.2.7. Electrical connections  
The control for changing over to the passing beam(s) shall switch off the driving beam(s) simultaneously.
- 6.2.8. Tell-tale  
Optional; non-flashing green signal lamp.
- 6.2.9. Other requirements  
None.

**6.3. DIRECTION-INDICATOR LAMP**

- 6.3.1. Number  
Two per side.
- 6.3.2. Arrangement  
Two front indicators (category 1 as specified in Regulation No. 6 or category 11 specified in Regulation No. 50).  
Two rear indicators (category 2 as specified in Regulation No. 6 or category 12 specified in Regulation No. 50).
- 6.3.3. Position

6.3.3.1. in width: For front indicators, the following requirements shall all be met:

1. there shall be a minimum distance of 240 mm between illuminating surfaces,
2. the indicators shall be situated outside the longitudinal vertical plane tangential to the outer edges of the illuminating surface of the headlamp(s),
3. there shall be a minimum distance between the illuminating surface of the indicators and passing beam headlamp closest to one another as follows:

Minimum Indicator intensity (cd)	Minimum Separation (mm)
90	75
175	40
250	20
400	≤20

For rear indicators, the clearance between the inner edges of the two illuminating surfaces shall be at least 180 mm on the condition that the prescriptions of paragraph 2.11. are applied even when the registration plate is mounted;